



## GH1202

Handheld GPS/GSM Tracker

#### Homecare.

Children, old people, pets etc. tracking and personal security.

#### Security.

GeoFence function, emergency calls (E112, E911).

#### Business.

Employees, cars, goods real-time tracking and protection, command and control from Monitoring Center.

- \* Protect your children!
- \* Take care of your pets!
- \* Search and rescue (SAR)!
- \* Protect your rental devices!
- \* Manage and secure your fleet and workforce!

#### ENJOY POCKET-SIZE AND LIGHT-WEIGHT!

Teltonika HandHeld Tracker is a handheld terminal with GSM and GPS connectivity, which is able to get device coordinates and transfer them via GSM network. No installation is required. This device is perfectly suitable for applications where location acquirement of remote objects is needed and perfectly suites for securing company's assets. Small size, long lifetime, mobility and universal configuration of the device ensures wide spectrum of its application: from people tracking, track control to special or secret tasks. GeoFence function allows to set restricted goegraphic areas and device will send warning messages whenever the object crosses the zone (in or out). Device can be used as USB GSM modem. High GPS receiver sensitivity makes device easy to integrate in any environment where ordinary GPS receivers can not fix their position. The whole of the mentioned advantages makes this solution very attractive for companies which success depends on quality of transportation, logistics and movable object monitoring.



# GH1202

Handheld GPS/GSM Tracker

### What you get:

- \* Combination of GPS and GSM wireless networks.
- \* Device configuration by SMS or from PC.
- \* Secure property via Geofence Protection.
- \* Real-Time tracking from the Internet.
- \* Device works in Sleep, Logging and Alarm modes.
- \* Low Battery notification by SMS.
- \* USB GSM Modem function.

#### Package contents:

- \* GH1202 Handheld Tracker
- \* CD with Software
- \* USB-Cable
- \* Screwdriver
- \* Battery
- \* Lineyard
- \* User Manual
- \* 220V Charger

TELTONIKA UAB Saltoniskiu str. 10C, LT-08105, Vilnius, Lithuania Phone: +370 5 2127472 Fax: +370 5 2761380 info@teltonika.lt www.teltonika.eu

#### **GH1202** Specifications:

GPS receiverSiRF Star III 2Internal GPS antennaPatchGSM frequencies (MHz)900/1800 850Voice callsYESVibroYESKeyboard5Lock for keyboardYESBattery1050mAh (Li-LED indicators3: Battery, CWeight80gDimensions (mm)92 x 44 x 18Data transferGPRSTCP/IPYESSMSOptionalTransmission of NMEAUSB (0183)	0/1900 -ion)			
GSM frequencies (MHz)900/1800 850Voice callsYESVibroYESKeyboard5Lock for keyboardYESBattery1050mAh (Li-LED indicators3: Battery, CWeight80gDimensions (mm)92 x 44 x 18Data transferGPRSTCP/IPYESSMSOptional	-ion)	/Alarm		
(MHz)90071800 850Voice callsYESVibroYESKeyboard5Lock for keyboardYESBattery1050mAh (Li-LED indicators3: Battery, CWeight80gDimensions (mm)92 x 44 x 18Data transferGPRSGPRSYESTCP/IPYESSMSOptional	-ion)	/Alarm		
VibroYESKeyboard5Lock for keyboardYESBattery1050mAh (Li-LED indicators3: Battery, GWeight80gDimensions (mm)92 x 44 x 18Data transferGPRSGPRSYESTCP/IPYESSMSOptional	-	/Alarm		
Keyboard5Lock for keyboardYESBattery1050mAh (Li-LED indicators3: Battery, CWeight80gDimensions (mm)92 x 44 x 18Data transferGPRSTCP/IPYESSMSOptional	-	/Alarm		
Lock for keyboardYESBattery1050mAh (Li-LED indicators3: Battery, GWeight80gDimensions (mm)92 x 44 x 18Data transferGPRSGPRSYESTCP/IPYESSMSOptional	-	/Alarm		
Battery1050mAh (Li-LED indicators3: Battery, CWeight80gDimensions (mm)92 x 44 x 18Data transferGPRSGPRSYESTCP/IPYESSMSOptional	-	/Alarm		
LED indicators3: Battery, CWeight80gDimensions (mm)92 x 44 x 18Data transfer92 x 44 x 18GPRSYESTCP/IPYESSMSOptional	-	/ Alarm		
Weight80gDimensions (mm)92 x 44 x 18Data transfer92 x 44 x 18GPRSYESTCP/IPYESSMSOptional	GSM, GPS	/ Alarm		
Dimensions (mm)92 x 44 x 18Data transfer92 x 44 x 18GPRSYESTCP/IPYESSMSOptional				
Data transferGPRSYESTCP/IPYESSMSOptional				
GPRSYESTCP/IPYESSMSOptional				
TCP/IP YES SMS Optional				
SMS Optional		YES		
	YES			
Transmission of NMEA LISB (0183)				
Connection to a PC				
USB YES				
Configuration				
Configuration via USB YES				
Configuration via SMS YES	YES			
Memory				
Internal memory 1MB	1MB			
Other				
Recommended operating 0 up to 50°C temperature	0 up to 50°C			
Storage temperature -20 up to 60	-20 up to 60 °C			
BATTERY LIFE TIME				
	Duty Cycle	Life Time (Hrs)		
0 86400	80%	24		
1 144	10%	102		
48 144	43%	72		
1440 1440	<b>9</b> 3%	26		