

Advanced Vehicle GPS Tracker



Harsh acceleration/ braking alert

Within 3-axis accelerometer, harsh acceleration/braking alarm can be realized.

Mobileye Fleet Safety

Compatible with Mobileye collision avoidance system to keep your drivers and assets safe.

Garmin Fleet Tracking

Streamline dispatching with Garmin intergration to further improve business efficiencies.



•



Multifunctional

Support CAN bus, camera, LED display, fuel/temperature sensor, iButton.

APPLICATION







Garbage truck



Armor cash carrier

Ambulance

SPECIFICATIONS

ITEM	SPECIFICATIONS
Dimension	105 mm x 65 mm x 26 mm
Weight	190g
Power supply	DC 11–36 V/1.5 A
Backup battery	400 mAh/3.7 V
Power consumption	Current in standby mode: 65mA
Operating temperature	-20°C to 55°C
Operating humidity	5% to 95%
Working hour	53 hours in power-saving mode 5.5 hours in normal mode
LED indicator	Green indicator showing the GSM signal Blue indicator showing the GPS signal
Button/Switch	1 power button
Memory	8 MB buffer
Sensor	3-axis accelerometer (used to wake the device up by vibration and detect towing alarms)
Frequency band	GSM/GPRS: 850/900/1800/1900 MHz
GPS sensitivity	-161 dB
Positioning accuracy	2.5m
I/O port	3 digital inputs (1 negative trigger, 1 positive trigger, and 1 positive/negative selectable trigger) 2 analog detection inputs 2 outputs 1 RS232 EXT port 1 RS232/485 port 1 USB port 1 CAN bus interface 1-Wire® iButton 1-Wire® temperature sensor



ACCESSORIES

T622 with a built-in battery GPS antenna GSM antenna I/O cable USB cable CD download card



Camera iButton LLS sensor LED display A76 ultrasonic fuel level sensor Garmin navigator A53 fuel level sensor A52 digital temperature sensor + A61 sensor box



RoHS





+86(755)83462818





info@meitrack.com

6/F, West Tower, Cafu Plaza (Sheraton Hotel), No. 5, Guihua Rd., Futian Free Trade Zone, Shenzhen, China. 518038